



TUONO 125 - TECHNICAL SPECIFICATIONS

ENGINE	Single cylinder, 4-stroke, liquid cooled electronic injection, 4 valves double overhead camshaft (DOHC)
DISPLACEMENT	124.2 cc
TELAIO	Aluminium perimeter frame
FRONT SUSPENSION	Upside-down fork with Ø 40 mm stanchions Wheel travel: 110 mm
REAR SUSPENSION	Asymmetrical swingarm Monoshock absorber with 120 mm wheel travel
FRONT BRAKE	Ø 300 mm stainless steel disc 4-piston radial callipers
REAR BRAKE	ABS Bosch 9.1ML Ø 218 mm stainless steel disc
FRONT WHEEL	Single piston calliper 6 split spoke wheel rim in lightweight alloy Tyre 100/80 ZR 17
REAR WHEEL	6 split spoke wheel rim in lightweight alloy. Tyre 130/70 ZR 17
SADDLE HEIGHT	810 mm
FUEL TANK CAPACITY	14.5 lt - 4 reserve
DRY WEIGHT	129 kg
WET WEIGHT	144 kg
EMISSIONS COMPLIANCE	Euro 4
EMISSIONS	63 g/km (CO ₂)
CONSUMPTION	2.71 l/100km
ELECTRONIC MANAGEMENT	Aprilia Mia (multimedia platform) predisposition
COLOUR RANGE	Red Hero, Dark Warrior